



# Falcon USHA SNMP/HTTP Agent

Supports TCP/IP Based Remote UPS Monitoring & Management

## Advanced Features:

- \* Internet Based Remote UPS Monitoring & Management via LAN, WAN, Internet, PDA or WAP mobile phone
- \* Compatible with all Falcon SG, SSG, FN, FH & XG Series™ UPS Models
- \* Installs in Minutes Inside the Falcon UPS
- \* 10/100 Ethernet Connectivity
- \* Communicate via HTTP, SNMP & Telnet
- \* Automatic Notifications via Email or IP Trap Addresses
- \* Full Event & History Logging
- \* SNMPv3 Compliance & Multi-Level & User Security
- \* IPv4 & IPv6 Compliant
- \* RFC1628 & USHA MIBs Supplied For Windows® & UNIX
- \* Remote Shutdown Client Software Provided with Unlimited License
- \* Compatible with Network Management Software (NMS)
- \* Java® Based Graphical Monitoring
- \* BOOTP, DHCP, WakeOnLAN & TFTP Updates Supported
- \* CE & FCC Compliant



## **Easily Installs Into Falcon UPS Models**

Falcon Electric's internal USHA SNMP/HTTP Agent facilitates remote UPS monitoring and management over any Ethernet LAN, Enterprise Network or the Internet. Simply install the agent board into the communications option slot of a Falcon SG, SSG, FN, FH or XG Series UPS and connect it to any Ethernet LAN. If a DHCP server is present, an IP address will automatically be assigned and you are ready to go. A static IP address may also be assigned to the agent. Enter the agent's IP address into any network connected web browser and the USHA's internal remote monitoring management website is displayed.

## **USHA, The Secure World-Wide Remote UPS Management Solution**

The USHA agent provides the convenience and cost benefits of centralized remote UPS management. Whether your company has ten Falcon UPS units or ten thousand, they can all easily be managed and monitored from a single location on a single workstation.

In addition to the HTTP web interface, the USHA supports Simple Network Management Protocol (SNMP), allowing the use of any Network Management Software (NMS) with the installation of the supplied RFC1628 compliant MIB software.

The latest SNMPv3 level security has been incorporated. Both IPv4 and IPv6 IP addressing and security are also supported.

Your central workstation can be automatically notified of remote site power outages and events by listing management workstation's IP trap addresses, or by email.

## **Safely Shut Down Multiple Servers or Workstations**

Shutdown client software is supplied that allows for the orderly remote shutdown of multiple servers or workstations over your network. Just install the client software, set the shutdown delay time and enter the IP address of the controlling UPS's USHA agent.

Shutdown client software is provided for the following operating systems:

- \* Windows® 9x/NT/2000/XP/2003 & Vista®
- \* SCO (OpenServer® & UnixWare®)
- \* Linux
- \* Novell NetWare®
- \* Sun Solaris® (SPARC and X86)
- \* HP UX®
- \* SCO® UNIX
- \* FreeBSD

All shutdown client software is shipped with the USHA agent board and may be installed on as many servers and workstations as desired without any additional licensing costs.

## **Event & History Data Logging**

The USHA agent board stores power event and other important data in the following logs:

- \* UPS History Log
- \* UPS Extended Log
- \* UPS Event Log
- \* USHA Event Log

## **Unattended Event Scheduling**

The USHA agent board supports the following programmed scheduling:

- \* UPS Battery Test Scheduling
- \* Weekly UPS Shutdown & Restore Events
- \* Special Day UPS Shutdown & Restore Events

## **Advanced UPS Monitoring & Management Functions**

For a full list of monitoring and management functions supported, please reference the USHA Agent specifications on the following page.

**Falcon Electric, Inc.**

**5116 Azusa Canyon Road  
Irwindale, CA 91706**

**Toll-Free: 800-842-6940**

**Fax: 626-962-7720**

**Email: [sales@falconups.com](mailto:sales@falconups.com)**

**[www.falconups.com](http://www.falconups.com)**

# USHA SNMP/HTTP Agent Specification

Model Designation	USHA SNMP/HTTP Agent
<b>UPS Monitoring Functions</b>	
UPS Status	On-line Mode, Bypass Mode or Alarm Mode
UPS Model	Falcon UPS Model Designation
UPS Firmware Revision	Revision
UPS Manufacturer	Falcon
Current Utility Line Voltage	AC Volts
Minimum Utility Line Voltage, Last 1 Minute	AC Volts
Maximum Utility Line Voltage, Last 1 Minute	AC Volts
Current Utility Frequency	Hz
UPS Output Voltage	AC Volts
UPS Output Frequency	Hz
UPS Output Load	% of UPS rated output
UPS Output VA	VA
Battery Capacity Remaining	% of battery capacity remaining
Current UPS Battery Voltage	DC Volts
UPS Internal Temperature	Degrees (C or F)
Next Scheduled UPS Off Time	dd/mm/yyyy
Next Scheduled UPS On Time	dd/mm/yyyy
UPS Input Voltage Rating	AC Volts
UPS Output Voltage Rating	AC Volts
UPS Battery Status	OK or Failed
Time Since UPS was on Battery Power	Seconds
Battery Capacity Remaining	%
Current Battery Voltage Per Cell	DC Volts
Battery Last Replaced Date	dd/mm/yyyy
UPS Output Source	Normal, Battery or Bypass
Last Alarm Condition	Day, month, year, time and description of the alarm condition
Number of Connected Software Clients	Integer

<b>UPS Programmable Functions</b>	
UPS Over Temperature Set Point	Set in degrees C or F
UPS Overload Set Point	Set in % of UPS output capacity
Last Battery Replace Date	Set dd/mm/yyyy
UPS Shutdown Delay	Set in seconds
UPS Sleep Time	Set in minutes
Battery Test Command	None, Quick Test, Test Until Low Battery, Timed Test, Cancel Test, Clear Test
Battery Test Time	Minutes
Scheduled UPS Battery Test	dd/mm/yyyy and time
UPS Shutdown Event Triggers	AC Fail, Low Battery, Overload, Over Temperature, Scheduled
UPS Shutdown Event Trigger Action	Warning Only, Client Shutdown, UPS Shutdown
Weekly Schedule Setup	Shutdown and Restart Days and Times
Special Day Schedule Setup	Shutdown and Restart Days and Times

<b>USHA Monitoring &amp; Programmable Functions</b>			
USHA System Date	dd/mm/yyyy	System Name	User Text
USHA System Time	hh:mm:ss	System Contact	User Text
IP Address	IPv4 or IPv6 formats	System Location	User Text
Gateway Address	IPv4 or IPv6 formats	USHA Polling Rate	Seconds
Subnet Mask	IPv4 or IPv6 formats	USHA Baud Rate	2400 bps
IP Auto Configure	IPv6	Default Language	English or Chinese
Link-Local Address	IPv6	Default Temperature Unit	°C or °F
Global Address	IPv6	BOOTP/DHCP	Enable or Disable
Prefix Length	IPv6	Ping Echo	Enable or Disable
Router Address	IPv6	Network Upgrade (UDP 69)	Enable or Disable
Telnet Connection	Enable, Disable and TCP Port	SNMP Support	Enable, Disable and UDP Port
HTTP Support	Enable, Disable and TCP Port	SNMP Version	SNMPv1 or SNMPv3
SNMP Trap Receivers	NMS IP Address, User Name, Trap Type, Severity and Description	SNMP/HTTP Access Control	NMS IP Address, Community and Access Type
Home Page Refresh Rate	Battery, Input, Output, Alarm & Client Groups	Wake On LAN Targets	MAC Address, Repeat and Interval times
Email Notification	Server, Account, Password, DNS & Time	UPnP Support	Enable or Disable
External Link Setup	Link Address, Text and Enable or Disable	Address Status	IPv6

<b>USHA Agent Card Technical Specification</b>	
CPU	16-bits AC1106 Fast Ethernet RISC Processor Phoenix Kernel
Memory	2MB (1Mbit x16) TFBGA Flash ROM 2MB (1Mbit x16) SDRAM
Serial Communications	Two UART Channels, one RJ-45, one Gold finger
LAN Controller	10/100 Mbit Ethernet controller
Network Connection	10/100 TX RJ-45 jack connector
RTC	Internal Real Time Clock
UPS Protocol	Megatec
Network Protocols	SNMP over UDP/IP, HTTP over TCP/IP, ARP, TFTP, SSH, SSL, NTP, ICMP
Supported MIB	UPS MIB (RFC1628), USHA MIB
Operating Temperature	10°C to 40°C
Operating Humidity	20-90% Non-condensing
Size (H x W x D)	0.6" x 2.36" x 2.59" (15.2 mm x 60 mm x 65.8 mm)
Weight	1.41 ounces (40 gm)
Regulatory Compliance	FCC Class B, CE Class B

©2008 Falcon® Electric, Inc. All rights reserved. Falcon® and the Falcon Electric logo are registered trademarks of Falcon Electric, Inc. All other brand names and trademarks are the property of their respective owners.

The information and specifications stated in this document are subject to change without notice.

01-22-2008